


Campanella tipo CM


per uso con catena e fune



Catena Ø mm		Codice	Dimensioni secondo mm			Peso Kg	W.L.L. Kg
L	V		D	B	L		
7	6	CMX 0706	13	110	60	0,34	2000
8	7	CMX 0807	16	110	60	0,53	2500
10	8	CMX 1008	18	135	75	0,915	4000
13	10	CMX 1310	22	160	90	1,60	6700
16	13	CMX 1613	26	180	100	2,46	10000
18	16	CMX 1816	32	200	110	4,14	14000
20	18	CMX 2018	36	260	140	6,22	17500
22	20	CMX 2220	40	300	160	8,95	22400
26	22	CMX 2622	45	340	180	12,82	26600
32	26	CM 3226	50	350	190	16,55	31500
36	32	CM 3632	60	400	200	27,01	45000
40	36	CM 4036	60	400	200	27,01	56000


Campanella tipo CMC/CNC

per uso catena




Catena Ø mm	Codice	(con schiaccia- mento)	Dimensioni secondo mm							Peso Kg	W.L.L. Kg
			D	P	L	D1	P1	L1	SxX		
6	CMCX 06		18	135	75	13	54	25		1,315	2000
7	CMCX 07		18	135	75	13	54	25		1,315	4000
8	CMCX 08		22	160	90	16	70	34		2,32	5300
10	CMCX 10		26	180	100	18	85	40		3,52	8000
13	CMCX 13		32	200	110	22	115	50		6,26	14000
16	CMCX 16		36	260	140	26	140	65		9,56	21200
20	CMCX 20		50	350	190	33	150	70		22,65	33600
22	CMCX 22		50	350	190	36	170	75		25,19	39900
7	CNC 07	CNC S 07	20	160	95	14	120	70	8x25	2,90	5500
8	CNC 08	CNC S 08	23	160	110	16	140	80	8x25	3,10	6650
10	CNC 10	CNC S 10	27	190	110	20	160	95	11,5x35	5,00	9400
13	CNC 13	CNC S 13	33	230	130	27	190	110	14x45	10,00	14200
16	CNC 16	CNC S 16	38	275	150	33	230	130	18x45	17,00	22300
20	CNC 20		45	340	180	38	275	150		27,80	33500
22	CNC 22		50	350	190	45	340	180		42,20	40800
26	CNC 26		60	400	200	50	350	190		60,10	56800

Catene grado 8



Tipo	Portata max ton*	Dim. in mm			Peso appr. Kg
		D	E	H	
D-7-8	1,6	7	21	10	1,1
D-8-8	2,0	8	24	11	1,5
D-10-8	3,2	10	30	13,5	2,3
D-13-8	5,3	13	39	19	3,9
D-16-8	8,0	16	48	24	5,7
D-20-8	11,5	19	59	28	7,6
D-22-8	15,0	22	65	31	11,0
D-26-8	21,2	26	78	35	15,2
D-32-8	32	32	96	46	23

Maglie di giunzione tipo GL



Tipo	Portata max ton*	Per catene di mm	Dim. in mm				Peso appr. Kg
			L	B	G	E	
GL-7/8-8	2,0	7,8	54	19,5	10	20,5	0,16
GL-10-8	3,2	10	68	25	12,5	27	0,35
GL-13-8	5,3	13	84	30	17	32	0,63
GL-16-8	8,0	16	103	36	21	40	1,05
GL-18/20-8	11,5	19	120	44	25	49	1,74
GL-22-8	15	22	142	53	28	55	2,75
GL-26-8	21,6	26	160	58	29	61	4,6
GL-32-8	32,0	32	200	70	36	78	8,6

La sicurezza nel sollevamento
con catene e componenti

LAGUNA FUNI